Luna Tri-Colour Wall Pack

External Range

CODE: LUNA-40TC/EM






Specification	Luna
System Power	40W (Emergency 3W)
Driver Manufacturer	Tridonic
LED Chipset	Samsung
Colour Rendering Index	>80
Lumen Output	4200Lm (Emergency 315Lm)
LED Efficacy	105 Lm/cW
Energy Saving	Integral Photocell Sensor
Power Factor	0.95
IP Rating	IP65
IK Rating	IK10
Colour Temperature	3000K / 4000K / 5000K
Beam Spread	125°
Housing Material	Aluminium
Diffuser Type	Polycarbonate
Operating Temperature	-20 to +65°C
Input Voltage	AC220-240V
Dimensions	308mm x 288mm x 182mm
Weight	2.7kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
Emergency Output	3 Hours (3W)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & ROHS


* Warranty terms and conditions apply

3HR Emergency **3W Battery**




TECHNICAL DRAWINGS





A = 308mm C = 182mm B = 288mm

LUMINOUS INTENSITY DISTRIBUTION



Information is subject to change and can be withdrawn without notice