

REBEL TRI-COLOUR BULKHEAD

RBL-R15-285TC

QVIS[®]
LIGHTING & SECURITY



15W
POWER

5YR*
WARRANTY

IP65

1350
LUMENS


Q-DRIVE

Driver as Standard


EPISTAR

LED's inside

TECHNICAL DRAWINGS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Specification	Rebel
System Power	15W
Driver Manufacturer	Q-Drive
LED Chipset	Epistar
Colour Rendering Index	>80
Lumen Output	1350Lm
LED Efficacy	90 Lm/cW
Dimmable	Contact Office
IP Rating	IP65
Power Factor	>0.9
Beam Spread	120 °
Colour Temperature	3000K/4000K/6000K
Operating Temperature	-20 to 40 °C
Weight	0.78kg
Dimensions	285mm x 86mm
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

* Warranty terms and conditions apply

● SURFACE & SUSPENDED RANGE