## REBEL TRI-COLOUR BULKHEAD

RBL-R15-285TC/EM







Specification	Rebel
System Power	15W (Emergency 3W)
Driver Manufacturer	Q-Drive
LED Chipset	Epistar
Colour Rendering Index	>80
Lumen Output	1350Lm (Emergency 270Lm)
LED Efficacy	90 Lm/cW
Dimmable	Contact Office
IP Rating	IP65
Power Factor	>0.9
Beam Spread	120 °
Colour Temperature	3000K/4000K/6000K
Operating Temperature	-20 to 40 °C
Weight	0.78kg
Dimensions	ø285mm x 86mm
Emergency Output	3 Hours (3W)*
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000- 3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

<sup>\*</sup> Warranty terms and conditions apply














**EPISTAR** 


Driver as Standard

LED's inside

## TECHNICAL DRAWINGS



## LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



<sup>\*</sup>For emergency products with a rated service life of < 50.000 operating hours, QVIS offers a 5-year warranty period on the luminaire and 1-year warranty period on the battery pack