Taurus Tri-Colour Bulkhead

Surface & Suspended Range

CODE: TAU-16-325TC/TE


























TECHNICAL DRAWINGS

A	



A = 325mm B = 109mm

LUMINOUS INTENSITY DISTRIBUTION



System Power

Driver Manufacturer	Tridonic
LED Chipset	Epistar
Colour Rendering Index	>80
Lumen Output	1680Lm (Emergency 315Lm)
LED Efficacy	105 Lm/cW
Power Factor	>0.9
Dimmable	DALI / Switch-Dim / Corridor / DSI
IP Rating	IP65
IK Rating	IK10
Colour Temperature	3000K / 4000K / 6000K
Housing Material	Polycarbonate
Diffuser Material	Polycarbonate
Operating Temperature	-20 to +40 °C
Input Voltage	AC220-240V
Dimensions	325mm x 109mm
Weight	0.89kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 [Ta 25 °C]
Emergency Output	3 Hours (3W)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & ROHS

16W (Emergency 3W)

Specification Taurus

^{*} Warranty terms and conditions apply