Vex Tri-Colour Commercial Bulkhead

Surface & Suspended Range

CODE: VEX-20-360TC/QE



























TECHNICAL DRAWINGS





A = 360mm B = 105 mm

LUMINOUS	INTENSITY	DISTRIBUTION
150"	180"	150"



Information is subject to change and can be withdrawn without notice

Specification Vex System Power 20W [Emergency 3W] Driver Manufacturer Q-Drive LED Chipset Samsung Colour Rendering Index >80 Lumen Output LED Efficacy 105 Lm/cW (Emergency 315Lm) Power Factor Dimmable DALI / Switch-Dim / 1-10V IP Rating IP66 IK Rating IK10 Fire Rating Colour Temperature 3000K / 4000K / 6000K Housing Material Polycarbonate Diffuser Material Polycarbonate Operating Temperature -20 to +30 °C Input Voltage AC220-240V Dimensions 360mm x 105mm Weight MacAdam Step 50,000 hours, L70-B10 [Ta 25 °C] Lifetime **Emergency Output** CE Standards EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581 LVD, EMC, ERP & RoHS

^{*} Warranty terms and conditions apply