Vex Commercial Bulkhead

Surface & Suspended Range

Specification

System Power

LED Chipset

Lumen Output

LED Efficacy

Power Factor

Weight

Lifetime

MacAdam Step

Emergency Output CE Standards

CE Directives

Driver Manufacturer

Colour Rendering Index

CODE: VEX-25-420NW/QE























TECHNICAL DRAWINGS

A	



A = 420mm B = 112mm

Dimmable	DALI / Switch-Dim / 1-10V	
IP Rating	IP66	
IK Rating	IK10	
Fire Rating	TP(a)	
Colour Temperature	4000K	
Housing Material	Polycarbonate	
Diffuser Material	Polycarbonate	
Operating Temperature	-20 to +40 °C	
Input Voltage	AC220-240V	
Dimensions	420mm x 112mm	

1.6kg <3

50,000 hours, L70-B10 [Ta 25 °C]

LVD, EMC, ERP & RoHS

EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581

Vex

Q-Drive

Samsung


2700Lm

>80

25W (Emergency 3W)

108 Lm/cW (Emergency 324Lm)

LUMINOUS INTENSITY DISTRIBUTION



Information is subject to change and can be withdrawn without notice