Vex Commercial Bulkhead

Vex

Tridonic

Samsung

2700Lm

>80

IP66

IK10

TP(a) 4000K

Polycarbonate

Polycarbonate -20 to +40 °C

AC220-240V

1.6kg

<3

420mm x 112mm

50,000 hours, L70-B10 [Ta 25 °C]

EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581 LVD, EMC, ERP & RoHS

25W (Emergency 3W)

108 Lm/cW [Emergency 324Lm]

DALI / Switch-Dim / Corridor / DSI

Surface & Suspended Range

Specification

System Power

LED Chipset

Lumen Output

LED Efficacy

Power Factor Dimmable

IP Rating

IK Rating

Fire Rating

Colour Temperature Housing Material

Operating Temperature

Diffuser Material

Input Voltage

Dimensions

Weight MacAdam Step

Lifetime

Emergency Output CE Standards

Driver Manufacturer

Colour Rendering Index

CODE: VEX-25-420NW/TE
























TECHNICAL DRAWINGS

A
1



LUMINOUS INTENSITY DISTRIBUTION





















^{*} Warranty terms and conditions apply