## NCF Robust Vapour Proof Linear



CODE: NCF2-35-1200NW/EM








## **TECHNICAL DRAWINGS**

А

Specification	NCF
System Power	35W [Emergency 3W]
Driver Manufacturer	Tridonic
LED Chipset	Samsung
Colour Rendering Index	>85
Lumen Output	4200Lm (Emergency 360Lm)
LED Efficacy	120 Lm/cW
Power Factor	0.958
Dimmable	On Request
IP Rating	IP65
Colour Temperature	4000K
Beam Spread	120°
Housing Material	Polycarbonate
Diffuser Material	Polycarbonate
Operating Temperature	-20 to +65 °C
Input Voltage	AC200-240V, 47-63Hz
Dimensions	1260mm x 110mm x 73mm
Weight	2.05kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
Emergency Output	3 Hours (3W)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

в ; с A = 110mm C = 1260mm B = 73mm

## LUMINOUS INTENSITY DISTRIBUTION



\* Warranty terms and conditions apply

## Information is subject to change and can be withdrawn without notice