


# Phoenix Architectural Panel (6x6)


Modular & Recessed Range

CODE: PHO-30-6X6NW/QD

**QVIS**<sup>®</sup>  
LED LIGHTING



## TECHNICAL DRAWINGS




A = 595mm    C = 55mm  
B = 595mm

Specification	Phoenix
System Power	30W
Driver Manufacturer	Q-Drive
LED Chipset	Epistar
Colour Rendering Index	>85
Typical UGR	<19
Lumen Output	3300Lm
LED Efficacy	110 Lm/cW
Power Factor	>0.9
IP Rating	IP40
Diffuser	Opal
Dimmable	DALI / Switch-Dim / 1-10V
Beam Spread	78°
Colour Temperature	4000K
Housing Material	Polycarbonate
Operating Temperature	-20 to +45 °C
Input Voltage	AC220-240V, 50-60Hz
Dimensions	595mm x 595mm x 55mm
Weight	3kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

\* Warranty terms and conditions apply

## LUMINOUS INTENSITY DISTRIBUTION



**Information is subject to change and can be withdrawn without notice**

For further information on our products or terms and conditions visit our website [www.qvis.co.uk/lighting](http://www.qvis.co.uk/lighting) or email: [sales@qvislighting.com](mailto:sales@qvislighting.com)