

Clarus EVO Custom Downlight (228mm)

Downlight Range

CODE: CLE-35-228-FR-NW

QVIS[®]
LED LIGHTING



A RANGE OF REFLECTORS AND
DROP-GLASS ATTACHMENTS ARE AVAILABLE
[SOLD SEPERATELY]



35W
Power


7YR
Warranty



3850
Lumens


Specification	Clarus EVO
System Power	35W
Driver Manufacturer	Tridonic
LED Chipset	Citizen
Colour Rendering Index	>80
Typical UGR	<19
Lumen Output	3850Lm
LED Efficacy	110 Lm/cW
Power Factor	0.9
IP Rating	IP54
IK Rating	IK06
Dimmable	On Request
Beam Spread	60°
Colour Temperature	4000K
Housing Material	Aluminium & Polycarbonate
Reflector Type	Faceted
LED Type	COB
Operating Temperature	-20 to +45 °C
Input Voltage	AC200-240V
Cut Out Diameter	200-210mm
Dimensions	228mm x 99mm
Weight	1.135kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3- 3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

TECHNICAL DRAWINGS



A = 228mm B = 99mm

LUMINOUS INTENSITY DISTRIBUTION



* Warranty terms and conditions apply

Information is subject to change and can be withdrawn without notice

For further information on our products or terms and conditions visit our website www.qvis.co.uk/lighting or email: sales@qvislighting.com