


# Helios Slimline Downlight (110mm)

Downlight Range


CODE: H65-10-110WW

**QVIS**<sup>®</sup>  
LED LIGHTING




Specification	Helios
System Power	10W
Driver Manufacturer	Osram
LED Chipset	Samsung
Colour Rendering Index	>85
Typical UGR	<19
Lumen Output	1150Lm
LED Efficacy	115 Lm/cW
Power Factor	0.9
IP Rating	IP65
Fire Rating	TP(a)
Diffuser	Opal
Dimmable	On Request
Beam Spread	90°
Colour Temperature	3000K
Housing Material	High Grade 6063 Aluminium Frame
Diffuser Material	Polycarbonate
Operating Temperature	-20 to +65 °C
Input Voltage	AC200-240V, 50-60Hz
Cut Out Diameter	95mm
Dimensions	110mm x 24mm
Weight	0.3kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

## TECHNICAL DRAWINGS



## LUMINOUS INTENSITY DISTRIBUTION



\* Warranty terms and conditions apply

**Information is subject to change and can be withdrawn without notice**

For further information on our products or terms and conditions visit our website [www.qvis.co.uk/lighting](http://www.qvis.co.uk/lighting) or email: [sales@qvislighting.com](mailto:sales@qvislighting.com)