


# Lynx Modular Panel (12x6)


Modular & Recessed Range

CODE: LYNX-SLG-40-12X6WW

**QVIS**<sup>®</sup>  
LED LIGHTING



## TECHNICAL DRAWINGS




A = 595mm C = 1195mm  
B = 10.5mm

Specification	Lynx
System Power	40W
Driver Manufacturer	Osram
LED Chipset	Samsung
Colour Rendering Index	>85
Typical UGR	<17
Lumen Output	4800Lm
LED Efficacy	120 Lm/cW
Power Factor	0.95
IP Rating	IP44 from Below
Diffuser	Microprism
Dimmable	On Request
Beam Spread	160°
Colour Temperature	3000K
Housing Material	High Grade 6063 Aluminium Frame
Light Guide Plate	PMMA
Operating Temperature	-20 to +45 °C
Input Voltage	AC200-240V, 47-63Hz
Dimensions	1195mm x 595mm x 10.5mm
Weight	8.5kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

\* Warranty terms and conditions apply

## LUMINOUS INTENSITY DISTRIBUTION



**Information is subject to change and can be withdrawn without notice**

For further information on our products or terms and conditions visit our website [www.qvis.co.uk/lighting](http://www.qvis.co.uk/lighting) or email: [sales@qvislighting.com](mailto:sales@qvislighting.com)