


LYNX RECESSED MODULAR (12x3)

LYNX-ADV30-12X3CW/TD

QVIS[®]


LIGHTING & SECURITY




TRIDONIC
enlightening your ideas
Driver Manufacturer

SAMSUNG
LED's inside

TECHNICAL DRAWINGS



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Specification	Lynx Advance 12x3
System Power	30W
Driver Manufacturer	Tridonic
LED Chipset	Samsung
Diffuser	Opal
Colour Rendering Index	>85
Typical UGR	<19
LED Efficacy	130 Lm/cW
Lumen Output	3900Lm
Fire Rating	TP(a)
Dimmable	Dali / Switch-Dim / Corridor / DSI
Power Factor	0.95
IP Rating	IP44
Beam Spread	160 °
Colour Type	Single
Colour Temperature	6000K
Housing Material	High Grade 6063 Aluminium
Light Guide Plate	PMMA
Operating Temperature	-20 to 50 °C
Input Voltage	AC 200-240V, 47-63Hz
Weight	2.7kg
Dimensions	1195mm x 295mm x 12mm
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

* Warranty terms and conditions apply



For further information on our products or terms and conditions visit our website
www.qvisled.com or email: sales@qvislighting.com

MODULAR & RECESSED RANGE