Orion High-Lumen Back-Lit Panel (6x6)

Modular & Recessed Range

CODE: ORN-BL-25-6X6NW
















Specification	Orion
System Power	25W
Driver Manufacturer	Osram
LED Chipset	Samsung
Colour Rendering Index	>85
Typical UGR	<19
Lumen Output	3800Lm
LED Efficacy	152 Lm/cW
Power Factor	0.95
IP Rating	IP44
Fire Rating	TP(a)
Diffuser	Opal
Dimmable	On Request
Beam Spread	160°
Colour Temperature	4000K
Housing Material	Aluminium
Operating Temperature	-20 to +50 °C
Input Voltage	AC200-240V, 47-63Hz
Dimensions	595mm x 595mm x 32mm
Weight	2.5kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-I, EN 60598 2-2, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3- 3, EN62722-I, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & ROHS

* Warranty terms and conditions apply

TECHNICAL DRAWINGS



A = 595mm C = 32mm B = 595mm

LUMINOUS INTENSITY DISTRIBUTION

