


QStorm Pro

Switchable Vapour Proof

CODE: QS-PRO-WS-1500TC/EM

- High LED Efficacy
- IK08 Impact Resistance
- Wattage Switchable
- Tri-Colour (3000K/4000K/5700K)

Dimensions



Power [Selectable]	Efficacy	Output	Kelvin
26W [Emergency 3W]	170Lm/cW	4420Lm [Emergency 510Lm]	Tri-Colour: 3000K, 4000K or 5700K
32W [Emergency 3W]	170Lm/cW	5440Lm [Emergency 510Lm]	
39W [Emergency 3W]	170Lm/cW	6630Lm [Emergency 510Lm]	
45W [Emergency 3W]	170Lm/cW	7650Lm [Emergency 510Lm]	

Technical

Input Voltage	AC 200-240V
Colour Rendering Index	>80
Beam Spread	120°
Power Factor	>0.9
Operating Temp.	-20 to +40°C
Materials	Polycarbonate
IP Rating	IP66
IK Rating	IK08
Dimmable	On Request
Dimensions	1523mm x 120mm x 76mm
Weight	2.49kg
MacAdam Step	<3
Lifetime	3 Hours [3W]
Lifetime	50,000 hours, L90-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

A T G **C** Light Source Energy Rating

Photometric Data

