


QStorm Pro

Switchable Vapour Proof

CODE: QS-PRO-WS-1800TC


- High LED Efficacy
- IK08 Impact Resistance
- Wattage Switchable
- Tri-Colour (3000K/4000K/5700K)

Dimensions



A
T
G **C** Light Source Energy Rating

Photometric Data



7 YEARS
WARRANTY
+ 2 YEAR ON SITE *

Power [Selectable]	Efficacy	Output	Kelvin
35W	170Lm/cW	5950Lm	Tri-Colour: 3000K, 4000K or 5700K
44W	170Lm/cW	7480Lm	
53W	170Lm/cW	9010Lm	
62W	170Lm/cW	10540Lm	

Technical

Input Voltage	AC 200-240V
Colour Rendering Index	>80
Beam Spread	120°
Power Factor	>0.9
Operating Temp.	-20 to +40°C
Materials	Polycarbonate
IP Rating	IP66
IK Rating	IK08
Dimmable	On Request
Dimensions	1823mm x 120mm x 76mm
Weight	2.68kg
MacAdam Step	<3
Lifetime	50,000 hours, L90-B10 [Ta 25 °C]
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS