

# COG5C-IP-AD-TUR-FW

## 5MP FULL-COLOUR AI DETERRANCE NETWORK TURRET



WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. WizSense provides intelligent, simple and inclusive products and solutions.

### Series Overview

With advanced deep learning algorithm, the WizSense 3 Series network camera supports intelligent functions, such as perimeter protection and smart motion detection. In addition, with full-colour technology, it provides a better image effect in the condition of low illuminance.

### Functions

#### SMD Plus

With intelligent algorithm, Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

#### Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, smart encoding technology realizes a higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.


#### Full-colour

With high-performance sensor and large aperture lens, Full-colour technology can display clear colourful imagery in the environment of ultra-low illuminance. With this photosensitivity technology, the camera can capture more available light, and display more colourful image details.

#### Siren and Light Active Deterrence

The siren and light active deterrence network camera supports light alarm and voice alarm when perimeter event occurs, to realize deterrence and effective intervention. The camera is built in multiple voices for selection, and supports customized voice importing.

- 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 5MP (2592 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in warm illuminator, and the max. illumination distance: 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.
- Supports sound and light alarm linkage. When an alarm is triggered, the camera links sound alarm and light flashing.
- Supports one-tap disarming. You can disarm the events of alarm output, sending email, audio, and light in the configured period.
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker
- 12V DC/PoE power supply
- IP67 protection
- SMD Plus
- Red and blue flashlight alarm



### Perimeter Protection

With deep learning algorithm, Perimeter Protection technology can recognize human and vehicle accurately. In restricted areas (such as pedestrian areas and vehicle areas), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

### Protection (IP67, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure works as normal after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows ±30% input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with unstable voltage.

## Technical Specification

### Camera

|                            |                                                   |
|----------------------------|---------------------------------------------------|
| Image Sensor               | 1/2.7"5Megapixel progressive CMOS                 |
| Max. Resolution            | 2592 (H) × 1944 (V)                               |
| ROM                        | 128 MB                                            |
| RAM                        | 512 MB                                            |
| Scanning System            | Progressive                                       |
| Electronic Shutter Speed   | Auto/Manual 1/3 s–1/100,000 s                     |
| Min. Illumination          | 0.003 Lux @ F1.0                                  |
| S/N Ratio                  | >56 dB                                            |
| Illumination Distance      | 30 m (98.4 ft)                                    |
| Illuminator On/Off Control | Auto/Manual                                       |
| Illuminator Number         | 1 (Warm light)                                    |
| Pan/Tilt/Rotation Range    | Pan: 0°–360°<br>Tilt: 0°–78°<br>Rotation: 0°–360° |

### Lens

|                      |                                                        |                   |                   |                  |                 |
|----------------------|--------------------------------------------------------|-------------------|-------------------|------------------|-----------------|
| Lens Type            | Fixed-focal                                            |                   |                   |                  |                 |
| Mount Type           | M12                                                    |                   |                   |                  |                 |
| Focal Length         | 2.8 mm                                                 |                   |                   |                  |                 |
| Max. Aperture        | F1.0                                                   |                   |                   |                  |                 |
| Field of View        | 2.8 mm: Horizontal 103° × Vertical 53° × Diagonal 122° |                   |                   |                  |                 |
| Iris Type            | Fixed                                                  |                   |                   |                  |                 |
| Close Focus Distance | 2.8 mm: 1.2 m (3.9 ft)                                 |                   |                   |                  |                 |
| DORI Distance        | Lens                                                   | Detect            | Observe           | Recognize        | Identify        |
|                      | 2.8 mm                                                 | 67.4 m (221.1 ft) | 27 m (88.6 ft)    | 13.5 m (44.3 ft) | 6.7 m (22.0 ft) |
|                      | 3.6 mm                                                 | 80.0 m (262.5 ft) | 32.0 m (105.0 ft) | 16.0 m (52.5 ft) | 8.0 m (26.2 ft) |

### Professional, intelligent

|                            |                                                                                                                  |
|----------------------------|------------------------------------------------------------------------------------------------------------------|
| IVS (Perimeter Protection) | Tripwire; intrusion (support the classification and accurate detection of vehicle and human)                     |
| Intelligent Search         | Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos. |

### Video

|                   |                                                                                                                                                                                                         |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Compression | H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)                                                                                                                                  |
| Smart Codec       | Smart H.265+/Smart H.264+                                                                                                                                                                               |
| Video Frame Rate  | Main stream: 2592 × 1944 @1-20 fps<br>2688 × 1520 @1-25/30 fps<br>Sub stream: 704 × 576 @1-25 fps/704 × 480 @ 1-20fps<br>Third stream: 1920 × 1080 @1-25/30 fps                                         |
| Stream Capability | 3 streams                                                                                                                                                                                               |
| Resolution        | 5M (2592 × 1944); 4M (2688 × 1520); 4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (354 × 288/354 × 240) |

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| Bit Rate Control         | CBR/VBR                                                    |
| Video Bit Rate           | H.264: 32 kbps–8192 kbps<br>H.265: 12 kbps–8192 kbps       |
| Day/Night                | Colour/B/W                                                 |
| BLC                      | Yes                                                        |
| HLC                      | Yes                                                        |
| WDR                      | 120 dB                                                     |
| Scene Self-adaptation    | Yes                                                        |
| White Balance            | Auto/natural/street lamp/outdoor/manual/regional custom    |
| Gain Control             | Auto/Manual                                                |
| Noise Reduction          | 3D DNR                                                     |
| Motion Detection         | OFF/ON (4 areas)                                           |
| Region of Interest (Rol) | Yes (4 areas)                                              |
| Smart Illumination       | Yes                                                        |
| Image Rotation           | 0°/90°/180°/270° (Support with 1080p resolution and lower) |
| Mirror                   | Yes                                                        |
| Privacy Masking          | 4 areas                                                    |

### Audio

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| Built-in MIC      | Yes                                                                   |
| Audio Compression | PCM; G.711a; G.711Mu; G.726; AAC; MPEG2-Layer2; G.722.1; G.729; G.723 |

### Alarm

|             |                                                                                                                                                                                                                                                                                                                           |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alarm Event | No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; scene changing; audio detection; voltage detection; external alarm; SMD; safety exception; light alarm; sound alarm (11 built-in sounds and custom voices importing) |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Network

|                     |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network             | RJ-45 (10/100 Base-T)                                                                                                                                                   |
| SDK and API         | Yes                                                                                                                                                                     |
| Protocol            | IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP |
| Interoperability    | ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec; P2P                                                                                                     |
| User/Host           | 20 (Total bandwidth: 80 M)                                                                                                                                              |
| Storage             | FTP; SFTP; Micro SD card (support max. 256 G); Dahua Cloud; NAS                                                                                                         |
| Browser             | IE: IE8 and later<br>Chrome<br>Firefox<br>Safari: Safari 12 and later                                                                                                   |
| Management Software | Smart PSS; DSS; DMSS                                                                                                                                                    |
| Mobile Phone        | iOS; Android                                                                                                                                                            |

### Certification

|               |                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------|
| Certification | CE-LVD: EN62368-1<br>CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU<br>FCC: 47 CFR FCC Part 15, Subpart B |
|---------------|-----------------------------------------------------------------------------------------------------------------------|

## Port

|              |                             |
|--------------|-----------------------------|
| Audio Input  | 1 channel (RCA port)        |
| Audio Output | 1 channel (RCA port)        |
| Alarm Input  | 1 channel in: 5mA 3V–5V DC  |
| Alarm Output | 1 channel out: 300mA 12V DC |

## Power

|                   |                                                                                                                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Supply      | 12V DC/PoE (802.3af)                                                                                                                                                                        |
| Power Consumption | Basic power consumption: 2.5W (12V DC); 3.0W (PoE)<br>Max. power consumption (WDR + H.265 + red and blue lights flashing alternately + warm light + sound alarm): 7.3W (12V DC); 8.0W (PoE) |

## Environment

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Operating Conditions | –40°C to +60°C (–40°F to +140°F)/Less than 95% RH |
| Storage Conditions   | –40°C to +60°C (–40°F to +140°F)                  |
| Protection Grade     | IP67                                              |

## Structure

|              |                                     |
|--------------|-------------------------------------|
| Casing       | Metal                               |
| Dimensions   | Φ122.0 mm × 110.9 mm (Φ4.8" × 4.4") |
| Net Weight   | 754 g (1.7 lb)                      |
| Gross Weight | 915 g (2.0 lb)                      |

## Dimensions (mm[inch])

