

## Cololight PLUS

Cololight PRO  
(Starter Set)

LS166A3

Main controller\*1

Cololight\*3

Plastic base\*1

Connector\*3

Ivory white

Led module: 86\*74.5\*30.5mm

Controller: 73.1\*45\*8.9mm

Plastic base: 168.2\*63.1\*23mm

Fixator: 16.5\*17.5\*9mm

Connector: 23.1\*17.5\*9mm

Led module: 52.5g

Controller: 30g

Plastic base: 35.5g

Fixator: 2g

Connector: 2.6g

Upper cover: ABS; others: ABS+PC



### General

Led Color	16 Million color
Operating Temperature	-5~45°C
Operating Humidity	5~90%
Power Supply	DC 5V 2A (each 10 light units require 1 ampere extra power)
Power Consumption	0.3W at lowest, max. <5W
Maximal Connecting Led Module	Up to 255 units per controller
Radio Protocol	Wi-Fi 2.4GHz
Touch Button	Yes, on the main controller
Number of LEDs Per Module	19 Led lights in one Cololight module, can be individually controlled
Features	app control, touch button control, bluetooth pairing, timer function, group control, play library for multiple effects



Scan QR For Direct Link To Download the FREE QLS Mobile App For Your Account & New Product Information, Product Demos & So Much More!