



Output



HD IPC



P2P



Network



PTZ



Audio



H.265



Mobile



CMS



x2 USB



Mouse



E-mail



6TB per HDD



32CHN HD PoE VIPER NVR

Features

- 32 CH H.265 NVR
- 8MP@25FPS
- 16 CHN Playback
- 16 PoE Ports
- 4 HDD
- Analytical Functions
- 1 Audio In / 1 Audio Out
- 4K x 2K Display
- 1 VGA + 1 HDMI
- 16 Alarms In / 4 Alarms Out
- RS485



SuperLive Plus

NOW AVAILABLE DIRECTLY THROUGH



SuperLive Plus is a professional mobile phone client software for digital video recorders and IP cameras in CCTV surveillance (compatible models only).

SPECIFICATION	VIPER-NVR-32
SYSTEM	
Compression	Standard H.265
OS	Embedded Linux
VIDEO	
Network Input	32 CH IPC Input
Network Access Bandwidth	256Mbps
Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps
Output	HDMI × 1 : 4K × 2K / 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024
AUDIO	
Network Input	32 CH IPC Audio Input
2-way Audio	RCA × 1
Local Output	RCA × 1
RECORD	
Record Stream	Dual Stream Recording
Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
Mode	Manual, Timer, Motion, Sensor
PLAYBACK	
Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted colour to display the camera record in a certain period of time, different colours refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
Analytics	
Functions	Motion detection, object detection, exception, tripwire, intrusion
ALARM	
Mode	Manual, sensor, motion, exception
Input	16 CH local alarm input, support 32 CH IPC alarm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.
Network	
Interface	RJ45 10 / 100 / 1000 Mbps × 1
PoE Port	RJ45 × 16
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Multiple users online
MOBILE DEVICE	
OS	iOS, Andriod
STORAGE	
HDD	SATA × 4, Max 6T per HDD
BACKUP	
Local Backup	U Disk, USB Mobile HDD
Network Backup	Yes
PORT	
USB	USB 2.0 × 1, USB 3.0 × 1 (one in the front panel and the other in the rear panel)
Remote Controller	Yes
OTHERS	
Power Supply	ATX
Consumption	≤ 30W (without HDD)
Dimensions (mm)	440 × 390 × 70 (W × D × H)
Work Environment	-10 - 50°C, 10% - 90% Humidity



Click here to view our website: www.qvisglobal.com, email: sales@adata.co.uk Sales Line: 023 92 488300.