



QVIS® 4-in-1 STARLIGHT VANDAL DOME

AHD

TVI

CVI

CVBS

FULL HD
1080

Model No.	QS-VAN-VFW
Image Sensor	1/2.8" Starlight & WDR CMOS Sensor
Signal System	PAL / NTSC
Active Pixels	1920 (H) x 1080 (V)
Lens	2.8-12mm MP Lens
Angle of View	H: 98° - 32°
Frame Rate	1080P @ 25 fps (50Hz), 1080P @ 30fps (60Hz)
Min Illumination	0 Lux (IR ON - IR-cut technology)
Menu	UTC Control
Video Output	CVBS / CVI / AHD / TVI ** Factory Default is TVI
Language	ENG / CHN / GER / FRA / ITA / SPA / POL / RUS / POR / NED / TUR / JPN / KOR / HEB / ARB
WDR	True WDR, 120dB
Backlight	BLC / HSBLC / WDR / Off
Mirror	Mirror / V-Flip / Rotate / Off
Day & Night	Colour / B&W / Auto / Ext
3-DNR	Low / Middle / High / Off
Exposure	Shutter / AGC / Sens-up / Brightness / Defogging
Auto Electronic Shutter	PAL:1/50 - 1/100,000 sec, NTSC:1/60 - 1/100,000 sec
Auto Gain Control	Built-in, value 0-15
Sens-up	On / Off
Brightness	Value 1-100
S/N Ratio	≥52 dB (AGC off)
Power Supply	DC12V ±10%
Current Consumption	80 mA(IR Off), 280 mA(IR On)
IR Led / Distance in Effect	30 pcs / 20-30M
IP Rating	IP66
Storage / Operating Temperature	-50°C ~ +90°C / -30°C ~ +70°C
Weight & Dimension	Approx 800g / Φ145*115mm

Utilising Sony Starvis Technology



SONY
STARVIS



NON SONY STARVIS

