



QVIS® | 4-IN-1 PTZ CAMERA

4 IN ONE IR HIGH SPEED DOME CAMERA

KEY FEATURES

- 2.0 MP HD-AHD/CVI/TVI/CVBS
- 100M IR Distance
- OSD Menu in English
- 256 preset points
- Pan Range: 360° continuous rotation
- Tile Range: -10°~90° with auto flip
- Manual Speed: Horizontal: 0.01°/s - 350°/s, Vertical: 0.01°/s - 120°/s
- Preset Speed: Pan: 350°/s, Tile: 120°/s
- Video Analysis Light-Adjustment Technology
- IP 66 all-environments protection

SPECIFICATION	PTZ-4IN1-20A
CAMERA	
Image Sensor	1/2.8" CMOS Sensor
Video	BNC (AHD / CVI / TVI / CVBS)
Resolution	1080P(1920x1080)
Optical Zoom	20X Optical Zoom
IRIS	Fix
IR-CUT	Auto / Manual
Electronic Shutter	1/1 ~ 1/10,000s
Min Illumination	0.05 Lux (Colour), 0.01 Lux (B/W)
Focal Length	4.9~97mm
Day / Night	On / Off / Auto
BLC	ON / OFF
White Balance	Auto / Manual
Noise Reduction	2DNR / 3DNR
Pan Range	360°
Tile Range	Range -10°~90°
Manual Speed	Horizontal: 0.01°/s - 350°/s, Vertical: 0.01°/s - 120°/s
Preset Speed	Pan: 350°/s Tile: 120°/s
Preset	256
Auto Cruising	8 groups (32 Preset / group)
Auto Scan	8 groups (setup left and right boundary)
Pattern Scanning	4 groups
Wiper	Optional
Bracket	Wall mount / Pendant mount
OSD Menu	English / Chinese
Timing Function	Support
Power Supply	AC24V±10%
Power Consumption	≤60W
Working Temp	-35°C ~ +60°C
Working Humidity	<90%, no condensing
Protection Level	IP66, the secondary lightning protection, 3000V anti-surge design
Size	5 Inch
Weight	5.8kg

