



QVIS® | 64 CHANNEL NVR

KEY FEATURES

- Support 32 / 64 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorisation management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

SPECIFICATION	VIPER-NVRPRO-64
System	
Compression	Standard H.265
OS	Embedded Linux
Video	
Network Input	64 CH IPC input
Network Access Bandwith	320Mbps
Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps
Output	HDMI × 2 : one of 4K × 2K / 1920 × 1080 / 1280 × 1024 the other is 1920 × 1080 / 1280 × 1024 VGA × 1 : 1920 × 1080 / 1280 × 1024
Audio	
Network Input	64 CH IPC audio input
2-way Audio	RCA × 1
Local Output	RCA × 1
Record	
Record Stream	Dual stream recording
Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P
Mode	Manual, timer, motion, sensor
Playback	
Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted colour to display the camera record in a certain period of time, different colours refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	
Mode	Manual, sensor, motion, exception
Input	8 CH local alarm input, support IPC alarm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.
Network	
Interface	RJ45 10 / 100 / 1000 Mbps × 2
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Web Client	Max 10 users online
Mobile OS Device	
OS	iOS, Andriod
Storage / Backup	
HDD	SATA × 8, e-SATA × 2, max 8T per HDD
Local Backup	U disk, USB mobile HDD
Network Backup	Yes



QVIS® | 64 CHANNEL NVR

SPECIFICATION	VIPER-NVRPRO-64
Port	
USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel), USB 3.0 × 1 (rear panel)
Remote Controller	Yes
Others	
Power Supply	ATX
Consumption	≤ 15W (without HDD)
Dimensions (mm)	430 × 453 × 89 (W × D × H)
Working Environment	-10°C ~ +50°C, 10% ~ 90% humidity

