

POESWITCH-16/24

16/24 POE SWITCH



POESWITCH-16/24 SPECIFICATIONS

Model No.	POESWITCH-16	POESWITCH-24
PoE Ports	16 Ports	24 Ports
10/100/1000m RJ45 Ports	2 Ports	2 Ports
1000M SFP	2 Ports	
Store-and- Forward	Support	
Exchange Capacity	7.2Gbps	8.8Gbps
MAC Address Table	16K	
LED	Power(red); PoE In-Use(orange); 10/100/1000 LINK/ACT(green)	
Power Requirement	100-240V AC, 50/60Hz	
Power Consumption	300 Watts Max	
PoE Power Output	Per Port 52V DC, 570mA. Max. 30 Watts	
PoE Power Supply Type	1 /2(+), 3/6(-), Mode-A, End-Span	
PoE Power Budget	PoE Max. 270W	
Regulation Compliance	FCC Part 15 ClassA, CE	
Standard Compliance	IEEE802.3 IEEE802.31: 10Base-TX IEEE 802.3u: 10Base-TX IEEE 802.3ab: 1000Base-T IEEE 802.3z: 1000Base-X(Fiber) IEEE 802.3af: Power over Ethernet(Low power) IEEE 802.3at: Power over Ethernet(High power) IEEE 802.3x: Flow Control	
Operating	Temperature : 0-50 Degree C; Relative Humidity: 20-95%	
Storage	Temperature: -10-70 Degree C Relav • Humidity: 20-95% (non-condensing)	
Dimension	440x200x44mm, 1U height	
Data Transfer Rates	Ethernet 10Mbps Half Duplex, 20Mbps Full Duplex Fast Ethernet 100Mbps Half Duplex, 200Mbps1 Full Duplex Gigabit Ethernet 2000Mbps1 Full Duplex	
Network Media	10Base-T: 2pairs of Cat3 or above UTP/STP (:1:100m) 10Base-TX: 2pairs of Cat5 or above UTP/STP(:1:100m) 1000Base-T:4pairs of Cat5e or above UTP/STP (:1:100m) 1000Base-SX: 82.5m/50m MMF(2m-550m) 1000Base-LX: 62.5m/50m MMF(2m-550m) or 10m SMF (2m-5000m)	