

DHI-LM49-S200

49" FHD Monitor



Features :

- Suitable for continuous 24/7 operation
- Using tamper-proof metal housing
- Slim 5.9mm narrow bezel design
- 8ms response time for no motion blur, judder or ghosting
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterrupted viewing angle
- Professional thermal design to extend equipment lifespan
- Built-in speakers, low energy consumption
- Support multiple signals, such as HDMI, CVBS, VGA, USB 2.0, Audio, RS232



Technical Specification

Model

Model	DHI-LM49-S200
-------	---------------

Display

Screen Size	49"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	380cd/m ²
Contrast	1200:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

Signals

Input	CVBS(BNC)×1, HDMI×1, VGA(D-Sub)×1, USB 2.0×2, DVI-D×1, Audio in×1, RS232(RJ45)×1, IR×1	
Output	CVBS×1, RS232(RJ45)×1, HDMI×2, VGA×1, Audio out×1	
	Speaker	10W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz, 1.5A
--------------	-------------------------------------

Consumption (Standard)	110W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	15kg(33.1lb)	
Gross Weight	29.4kg(64.8lb)	
Bezel Width	5.9mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1090.4×621.3×45.5mm (42.9"×24.5"×1.8")	
Package(W×H×D)	1265×850×270mm (49.8"×33.5"×10.6")	
Work Environment	Temperature	0℃~40℃ (32°F~104°F)
	Humidity	20%~85%

Accessory

Standard	HDMI cable, VGA cable, Power cable, Remote control, Hanging bracket
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

