

BULLETVIP4MPE3-FG-A

4MP FIXED E3 RANGE AI BULLET CAMERA



- 4MP (2592 × 1520)
- H.265+/H.265/H.264+/H.264 support
- AI functions (VSA people & vehicle, target counting, face detection, heat map)
- 3D DNR, WDR, HLC, BLC, ROI coding
- 20~30m IR distance
- DC12V/PoE power supply
- IP67 ingress protection
- Supports three streams
- Supports mobile surveillance by smart phones with iOS or Android OS
- Intelligent analytics

Specification	BULLETVIP4MPE3-FG-A			
Camera				
Image Sensor	1 / 3" CMOS			
Image Size	2592 x 1520			
Electronic Shutter	1/3s ~ 1 / 100000s			
Iris Type	Fixed Iris			
Min. Illumination	0.005 lux@F1.6,AGC ON; 0 lux with IR			
Lens	2.8mm@F1.6, Horizontal FoV: 95.3°; Vertical FoV: 53.2°; Diagonal FoV: 100.7°			
Lens Mount	M12			
Day & Night	ICR			
Wide Dynamic Range	120dB			
BLC	Yes			
HLC	Yes			
Defog	Yes			
Digital NR	3D DNR			
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80; Rotation: 0°~360°			
Image				
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG			
H.264 Compression Standard	Baseline Profile / Main Profile / High Profile			
Resolution	4MP [2592 x 1520], 2K [2560 x 1440], 3MP [2304 x 1296], 1080P [1920 x 1080], 720P [1280 x 720], D1, CIF, 480 x 240			
Main Stream	4MP/2K/3MP/1080P/720P[60Hz : 1 ~ 30fps; 50Hz: 1~25fps] HFR mode: 1080P/720P [60Hz : 1 ~ 60fps; 50Hz: 1~50fps]			
Sub Stream	720P/D1/CIF [60Hz : 1 ~ 30fps; 50Hz: 1~25fps]			
Third Stream	D1/CIF/480 x 240 [60Hz : 1 ~ 30fps; 50Hz: 1~25fps]			
Bit Rate	64 Kbps ~ 8 Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711A / U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Intelligent Analytics (Smart Events)				
Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/ motor vehicle/non-motor vehicle classification)			
Statistics	Target counting by line/area, heat map			
Exception Detection	Scene change, video blur and video cast detection			
Face Detection	Face detection and face capture			
Other Events	Abandoned/missing object detection			
DORI				
Lens	Detect	Observe	Recognise	Identify
	60.69m[199.11ft]	24.28m[79.65ft]	12.14m[39.82ft]	6.07m[19.91ft]
Interface				
Network	RJ45			
Audio	1CH audio input			
Storage	Built-in micro SD card slot, up to 256GB			
Reset	Yes			

BULLETVIP4MPE3-FG-A



- 4MP (2592 × 1520)
- H.265+/H.265/H.264+/H.264 support
- AI functions (VSA people & vehicle, target counting, face detection, heat map)
- 3D DNR, WDR, HLC, BLC, ROI coding
- 20~30m IR distance
- DC12V/PoE power supply
- IP67 ingress protection
- Supports three streams
- Supports mobile surveillance by smart phones with iOS or Android OS
- Intelligent analytics

Function	
Remote Monitoring	Web browsing
Web Browser	IE (plug-in required)/Google Chrome/Edge/Firefox/Safari
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card error, SD card full
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction, corridor pattern
Protection Grade	IP67
PoE	Yes (IEEE802.3af)
IR Distance	20 ~ 30 m
Others	
Power Supply	DC12V/PoE
Power Consumption	<6W
Operating Environment	-30°C ~ 60°C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	167.5 x 74.5 x 74.5
Weight (net)	Approx: 0.423kg
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH (EC1907/2006)

