

# PASSIVE HD VIDEO BALUN FOR CVI/TVI/AHD

# Titus

CODE: TT-105AP



Video Properties		HD-CVI / HD-TVI / AHD	
Transmission Signal		1-Channel	
Stability		>10,000h	
Transmission Distance	HD-CVI	720P: 400m	1080P: 250m
	HD-TVI	720P / 1080P: 250m	
	AHD	720P: 350m	1080P: 200m
Coaxial Video Connector		BNC-M	
Twisted-Pair Video Connector		Screw Interface	
Resolution		1080P / 720P	
Suggested Cable Type		CAT5/5E/6 (UTP)	
Anti-Interference		>60dB	
ESD Protection		1a Contact Discharge Electricity Level 3; 1b Air Discharge Electricity Level 3; Per: IEC61000-4-2	
Coaxial Cable Protection		2Kv (Common Code), Per: IEC1000-4-5	
UTP Cable Protection		2Kv (Differential Code); 4Kv (Common Code), Per: IEC1000-4-5	
BNC Male Impedance		75Ω	
UTP Cable Impedance		100Ω	
Material		Black ABS	

# PASSIVE HD VIDEO BALUN FOR CVI/TVI/AHD



CODE: TT-105AP

Storage Temperature	-20°C to +70°C (-4°F to +158°F)
Working Temperature	-10°C to +55°C (14°F to +131°F)
Working Humidity	Less than 95% (RH)