



Motorised Lens Bullet Camera

CODE: MBULLETVIP4K-VG-A



Motorised Zoom Lens



Triple Stream Support



50m IR Range



PoE Support

Camera

Image Sensor	1/2.5" CMOS
Video Compression	H.265+ / H.264+ / H.265 / H.264
Resolution	8MP, 2K, 3MP, 2MP (1 to 25fps)
Electronic Shutter	1/25s to 1/100,000s
Minimum Illumination	0.068 lux at F2.0 (AGC on); 0.024 lux at F1.2 (AGC on); 0 lux with IR
IR Range	50m
Lens	3.3mm to 12mm
Field of View	Horizontal: 97.5° to 38.5°
Focus	Motorised
Image Correction	BLC, HLC, WDR, Defog, Digital NR

Interfaces

Network	RJ45
Video	CVBS input (BNC x1); CVBS output (BNC x1)
Audio	1CH audio input; 1CH audio output
Alarm	1CH alarm input; 1CH alarm output
Storage	Micro SD card slot (supports up to 128GB)
Reset Button	Yes
RS485	Yes

Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 10 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF; GB-T/28181-2011



Motorised Lens Bullet Camera

CODE: MBULLETVIP4K-VG-A


IP

8^{4K}
MP

Functions (continued)

Alarm Events	Video Motion Detection, SD Card Error, SD Card Full
AI Events	Face Detection, Object Removal Detection, Abnormality Detection, People Intrusion Detection, People Counting, Crowd Density Detection, Region Intrusion Detection, Scene Change Detection, Line Crossing Detection,
Additional Functions	Watermark, Video Mask, Heartbeat, Password Protection

Compatible Accessories



Cable Management Ring

CODE: VIP-RING-06-WH

Parameters & Dimensions

Power Supply	DC12V / PoE
Power Consumption	< 9W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Dimensions	Ø108.9mm x 283.9mm
Weight	1.12kg
Installation	Ceiling or wall mounted
Protection Grade	IP67
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)