



Wireless Optical Smoke Alarm

CODE: QFS-ST-SA



Features

- Standalone wireless smoke alarm
- Photoelectric sensor to detect smoke quickly and reduce false alarms
- Compliant with EN14604:2005
- Alarm sounder (85dB)















Specification	QFS-ST-SA
Product Type	Photoelectric smoke detector
Working Voltage	DC 3V battery
Standby Current	<12uA
Alarm Current	<35uA
Low Voltage Threshold	2.7V
Product Life	10 years (5 year product warranty)
Interface	Test/hush button & LED indicator
Supplied In-Box	1x alarm, 1x manual, 1x mounting bracket, 2x anchor plug, 2x screws
Operating Temperature Range	0°C to +40°C



Wireless Optical Smoke Alarm

CODE: QFS-ST-SA

Functions

Normal	Red LED flashes once (50 seconds)	 
Low Voltage (Below 2.4V)	Red LED flashes once every 50 seconds, buzzer sound	 
Alarm	Continuous buzzer sound from device & rapid LED flashing	 
Mute (Hush)	Press the test to mute for 9 minutes. red LED flashes every 9 seconds	 
Test (Working)	Same as alarm mode. Indicates the alarm is in working order	 
Test (Fault Detection)	Eight red LED flashes without sound indicates abnormal functionality	 

WARNING

When the voltage is low, or service life reaches 10 years, the alarm should be replaced. In any doubt, an alarm trigger should be assumed to be due to a fire and appropriate measures must be taken immediately.

