

Wireless Heat Alarm

CODE: QFS-ST-HA



Features

- Standlone wireless heat alarm
- Thermistor sensor to detect temperature
- Compliant with BS5446-2:2003
- Alarm sounder (85dB)





Specification	QFS-ST-HA	
Product Type	Constant temperature detector	
Temperature Range to Trigger Alarm	54°C to 70°C	
Power Supply	3V Lithium sealed-In battery	
Product Life	10 years (5 year product warranty)	
Product Dimensions	(D)116mm x 46mm	
Alarm Indicator	Flashing red LED	
Auto-Reset	Supported	
Alarm Volume	Exceeds 85db at 3m range	
Protected Area	30sqm	





Wireless Heat Alarm

CODE: QFS-ST-HA

Functions

Normal	Green LED flash once (60 seconds)	6 0	4 ×
Fault	Red LED flashes twice every 60 seconds, buzzer sound	60	•
Low Voltage	Red LED flashes once every 60 seconds, buzzer sound	6 0	•
Alarm	Red LED flashes rapidly (every 0.1 seconds) with a buzzer - This continues until the temperature drops	•0•0•	•
Mute	In alarm mode, short press the test button to mute (this lasts for 9 minutes)	d × 9m	
Test	In normal mode, a short press activates a 9s light & sound alarm. Wait for 18s in order to test again	•0•0•	9 Ŷ



WARNING

When the voltage is low, or service life reaches 10 years, the alarm should be replaced. In any doubt, an alarm trigger should be assumed to be due to a fire and appropriate measures must be taken immediately.



